Interactive Whiteboards

RICOH Interactive Display D3210



RICOH imagine. change.

Maximise small space potential with multiplane high spec technology

The D3210 is ideal for use in huddle spaces where its feature rich capability can turn 1-2-1s into milestone moments worthy of the boardroom.

- Small and light with a 32" screen*
- Unique versatile mounting options vertical or flat
 plus 180° screen rotation**
- Superior touch screen sensitivity thanks to capacitance intelligence (PCAP)
- Compatible with Ricoh standard and smart controllers to customise functionality
- Easy to use with an intuitive UI just plug in, switch on and connect
- Sleek design, vivid display and easy access controls

^{*}D3210 display is available in white and black colours

^{**}Vertical option in portrait mode for Ricoh smart controllers only

Perfect for multiple huddle space uses

With superb visuals and an impressive suite of touch screen functionality, the D3210 enhances your customer-facing discussions by letting you manipulate content so it's a natural fit for estate agencies, banks, car dealerships, architects, developers and designers – to give just a few examples.

Also exploiting this interactive display's potential are schools, tutor groups, libraries, research centres and information points who use it to present ideas and explore subject matter.

As a dynamic shared surface, the D3210 is also an invaluable tool in the healthcare sector for both medical staff and patients.





Unique flip feature for table top interaction

The beauty of the D3210 is its size, weight and neat profile which make it the perfect solution for smaller meeting spaces. Add to that its physical versatility – it can be positioned vertically or laid flat to create an interactive table top. In both orientations, you've got the option of using the display either portrait or landscape should you choose to equip it with a Ricoh smart controller.

Designed to facilitate communication, stimulate thinking and boost productivity, the D3210 is powerfully versatile and can be dynamically orientated, making it the ideal solution for the 'huddle space' market.

Items Specifications			
Aspect ratio 16:9	Items		Specifications
Back light	Panel size		32" (31.5")
Max resolution [dot] 1920 x 1080 px (FHD) Max display colour 16.77 Million colours Brightness [cd/m²] (typ.) 500 Contrast ratio (typ.) 3000:1 Display orientation Landscape/Portrait/Flat Touch Technology PCAP Touch point Touch point Ricoh IWB app: 4 points Power supply voltage [V] 100-240V, 50-60Hz Power Lin operation Less than 295W (Fully configured) Standby Less than 0.3W Internal speaker Stereo (8+8) Audio Input L'R, RCA No Audio Output Speaker-out 1 (12W + 12W) Video Input UF, RCA No Speaker-out 1 (12W + 12W) Video Output DisplayPort 1 Viss Hub Port 4 ports Type A Power Supply Self Powered (7.5W) USB for touch OPS Slot Yes, supports Ricoh OPS controllers Product Size (W x D x H) [mm] 789 (W) x 70 (D) x 480 (H) Product Weight [kg] Installation VESA W200xH200mm	Aspect ratio		16:9
Max display colour Brightness [cd/m²] (typ.) Contrast ratio (typ.) Display orientation Touch Technology Touch point Power supply voltage [V] In operation Less than 295W (Fully configured) Consumption [W] Less than 0.3W Internal speaker Audio Input LR, RCA Audio Output Video Input Video Output DisplayPort Video Output DisplayPort Video Output USB Hub Port Power Supply Vess H) [Port Power 1 Power 2 Power 3 Power 3 Power 3 Power 4 Power 3 Power 4 Power 8 No Line 3.5mm 1 L/R, RCA No Speaker-out 1 (12W + 12W) VIDEO 1 VIDE	Back light		LED
Brightness [cd/m²] (typ.) 500 Contrast ratio (typ.) 3000:1 Display orientation Landscape/Portrait/Flat Touch Technology PCAP Touch:10 points Ricoh IWB app: 4 points Power supply voltage [V] 100-240V, 50-60Hz Power consumption [W] Standby Less than 295W (Fully configured) Internal speaker Stereo (8+8) Audio Input L/R, RCA No Audio Output Speaker-out 1 (12W + 12W) Video Input V/GA (Mini D-SUB 15pin) Video Output DisplayPort 1 Video Output DisplayPort 1 Video Output Port 4 ports Type A Power Supply Self Powered (7.5W) USB for touch 1 port Type B for touch control only OPS Slot Product Size (W x D x H) [mm] 789 (W) x 70 (D) x 480 (H) Product Weight [kg] VESA W200×H200mm	Max resolution [dot]		1920 x 1080 px (FHD)
Contrast ratio (typ.) Display orientation Touch Technology PCAP Touch point Power supply voltage [V] In operation Less than 295W (Fully configured) Consumption [W] Internal speaker Audio Input LR, RCA Audio Output Video Input Video Output DisplayPort Video Output DisplayPort Visit for touch OPS Slot Product Size (W x D x H) [mm] Product Weight [kg] I Touch 240V, 50-60Hz Lend 100-240V, 50-60Hz Less than 295W (Fully configured) Less than 0.3W Stereo (8+8) No Less than 0.3W Iters (8+8) No Stereo (8+8) 1 1 1 1 1 1 1 1 1 1 1 1 1	Max display colour		16.77 Million colours
Display orientation Touch Technology Touch point Power supply voltage [V] Power consumption [W] In operation Standby Internal speaker Audio Input Line 3.5mm Line 3.	Brightness [cd/m²] (typ.)		500
Touch Technology Touch point Touch point Touch point Touch:10 points Ricoh IWB app: 4 points Power supply voltage [V] Power consumption [W] In operation Standby Less than 295W (Fully configured) Less than 0.3W Internal speaker Audio Input LVR, RCA Audio Output VGA (Mini D-SUB 15pin) Video Input Video Output DisplayPort Video Output DisplayPort Video Output DisplayPort VF 3.0 Power Supply Vesh (W x D x H) [mm] Product Weight [kg] Internal 10-240V, 50-60Hz Loss than 295W (Fully configured) Less than 295W (Fully configured) Less than 295W (Fully configured) Vesh W209W (Fully configured) Vesh W200×H200mm	Contrast ratio (typ.)		3000:1
Touch point Touch:10 points Ricoh IWB app: 4 points	Display orientation		Landscape/Portrait/Flat
Ricoh IWB app: 4 points	Touch Technology		PCAP
Power consumption [W] In operation Less than 295W (Fully configured) Internal speaker Stereo (8+8) Audio Input L/R, RCA No Audio Output L/R, RCA No Speaker-out 1 (12W + 12W) Video Input VGA (Mini D-SUB 15pin) 1 Video Output DisplayPort 1 Video Output DisplayPort 1 Video Output DisplayPort 1 Video Output Port 4 ports Type A Power Supply Self Powered (7.5W) USB Hub Power Supply Self Powered (7.5W) USB for touch 1 port Type B for touch control only OPS Slot Yes, supports Ricoh OPS controllers Product Size (W x D x H) [mm] 789 (W) x 70 (D) x 480 (H) Product Weight [kg] <15 Installation VESA W200×H200mm	Touch point		·
Consumption [W] Standby Less than 0.3W	Power supply voltage [V]		100-240V, 50-60Hz
Internal speaker		In operation	Less than 295W (Fully configured)
Audio Input L/R, RCA No		Standby	Less than 0.3W
Audio Input Line 3.5mm 1 Audio Output L/R, RCA No Speaker-out 1 (12W + 12W) Video Input VGA (Mini D-SUB 15pin) 1 HDMI 1 DisplayPort 1 Video Output DisplayPort 1 VF 3.0 USB Hub Port 4 ports Type A Power Supply Self Powered (7.5W) USB for touch 1 port Type B for touch control only OPS Slot Yes, supports Ricoh OPS controllers Product Size (W x D x H) [mm] 789 (W) x 70 (D) x 480 (H) Product Weight [kg] <15 Installation VESA W200×H200mm	Internal speaker		Stereo (8+8)
Line 3.5mm	Audio Input	L/R, RCA	No
Audio Output Speaker-out 1 (12W + 12W) Video Input VGA (Mini D-SUB 15pin) 1 HDMI 1 DisplayPort 1 Video Output DisplayPort 1 USB Hub Port 4 ports Type A Power Supply Self Powered (7.5W) USB for touch 1 port Type B for touch control only OPS Slot Yes, supports Ricoh OPS controllers Product Size (W x D x H) [mm] 789 (W) x 70 (D) x 480 (H) Product Weight [kg] <15 Installation VESA W200×H200mm		Line 3.5mm	1
Speaker-out 1 (12W + 12W) VGA (Mini D-SUB 15pin) 1	Audio Output	L/R, RCA	No
D-SUB 15pin 1		Speaker-out	1 (12W + 12W)
HDMI	Video Input		1
Video Output DisplayPort 1 USB Hub VF 3.0 Port 4 ports Type A Power Supply Self Powered (7.5W) USB for touch 1 port Type B for touch control only OPS Slot Yes, supports Ricoh OPS controllers Product Size (W x D x H) [mm] 789 (W) x 70 (D) x 480 (H) Product Weight [kg] <15 Installation VESA W200×H200mm		HDMI	1
USB Hub Port 4 ports Type A Power Supply Self Powered (7.5W) USB for touch 1 port Type B for touch control only OPS Slot Yes, supports Ricoh OPS controllers Product Size (W x D x H) [mm] 789 (W) x 70 (D) x 480 (H) Product Weight [kg] <15 <17 (Fully configured) VESA W200×H200mm		DisplayPort	1
USB Hub Port 4 ports Type A Power Supply Self Powered (7.5W) USB for touch 1 port Type B for touch control only OPS Slot Yes, supports Ricoh OPS controllers Product Size (W x D x H) [mm] 789 (W) x 70 (D) x 480 (H) Product Weight [kg] <15 <17 (Fully configured) VESA W200×H200mm	Video Output	DisplayPort	1
Power Supply Self Powered (7.5W) USB for touch 1 port Type B for touch control only OPS Slot Yes, supports Ricoh OPS controllers Product Size (W x D x H) [mm] 789 (W) x 70 (D) x 480 (H)	USB Hub	I/F	3.0
USB for touch 1 port Type B for touch control only OPS Slot Product Size (W x D x H) [mm] Product Weight [kg] Installation 1 port Type B for touch control only Yes, supports Ricoh OPS controllers 789 (W) x 70 (D) x 480 (H) <15 <17 (Fully configured) VESA W200×H200mm		Port	4 ports Type A
OPS Slot Product Size (W x D x H) [mm] Product Weight [kg] Installation Yes, supports Ricoh OPS controllers 789 (W) x 70 (D) x 480 (H) <15 <17 (Fully configured) VESA W200×H200mm		Power Supply	Self Powered (7.5W)
Product Size (W x D x H) [mm] 789 (W) x 70 (D) x 480 (H) Product Weight [kg] <15 <17 (Fully configured) VESA W200×H200mm	USB for touch		1 port Type B for touch control only
Product Weight [kg] <15 <17 (Fully configured) VESA W200×H200mm	OPS Slot		Yes, supports Ricoh OPS controllers
Product Weight [kg] <17 (Fully configured) VESA W200×H200mm	Product Size (W x D x H) [mm]		789 (W) x 70 (D) x 480 (H)
<17 (Fully configured) VESA W200×H200mm	Product Weight [kg]		<15
Installation			<17 (Fully configured)
	Installation		



All company, brand, product and service names are the property of and are registered trademarks of their respective owners. Copyright © 2019 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/ or layout may not be modified and/or adapted, copied in part or in whole and/ or incorporated into other works without the prior written permission of Ricoh Europe PLC. Products available in 2019.