

P C375

MAIN SPECIFICATIONS

GENERAL

Warm-up time	32 seconds
First output speed: B/W	4.1 seconds
First output speed: full colour	5.3 seconds
Continuous output speed	A4/LEF (1-sided): B/W, full colour (32 cpm, 32 cpm) A4/LEF (2-sided): B/W, full colour (16 cpm, 16 cpm)
Memory: standard	2 GB
Weight	25 kg
Dimensions: W x D x H	410 x 429 x 360 mm
Power source	220 - 240 V, 50/60 Hz
Storage: standard	32 GB

PRINTER

CPU	QB6640-23UF 1.2GHz
Printer language: standard	PCL5c PCL6 PostScript 3 (emulation) PDF direct (emulation)
Printer language: option	Genuine Adobe® PostScript®3™ PDF Direct from Adobe®
Print resolution	1,200 x 1,200 dpi
Network interface: standard	Ethernet 10 base-T/100 base-TX/1000 base-T USB Host I/F Type A USB Device I/F Type B
Network interface: option	Wireless LAN (IEEE 802.11 a/b/g/n/ac) Additional NIC (2nd port)
Mobile printing capability	Apple AirPrint Mopria® Ricoh Smart Device Connector
Network protocol	TCP/IP (IP v4, IP v6)
Windows® environments	Windows® 10 Windows® 11 Windows® Server 2016 Windows® Server 2019 Windows® Server 2022
Mac OS environments	Macintosh OS X v10.15 or later

PAPER HANDLING

Recommended paper size	Standard paper tray(s): : A4, A5, A6, B5, B6 Optional paper tray(s): : A4, A5, B5, B6 Bypass tray: : A4, A5, A6, B5, B6, Envelopes, Custom Size paper (bypass tray): (Width: 76.2 mm - 216 mm, Length: 127 mm - 356 mm)
Paper input: standard	250 sheets
Paper input: bypass	50 sheets
Paper input: maximum	1,300 sheets
Paper output: standard	200 sheets
Paper weight	Trays: : 60 - 200 g/m² Bypass: : 60 - 200 g/m² Duplex: : 60 - 163 g/m²
Paper types	Plain paper Recycle paper Special paper Color paper Letterhead Envelope Label paper

ECOLOGY

Power consumption: max.	Less than 1,420 W
Power consumption operation: B/W	426.5 W
Power consumption operation: Full colour	441.7 W
Power consumption: ready	18.7 W
Power consumption: sleep	0.38 W
TEC*	0.32 kWh/week

* It is a reference value based on the ENERGY STAR Ver. 3.2 test method

INPUT/OUTPUT TRAYS AND FINISHER OPTIONS

1x 500-sheet Paper Tray

P C375

MAIN SPECIFICATIONS

OTHER OPTIONS

Cabinet, PostScript 3, Device server unit, Paperlock, Unicode Font Package for SAP, Wireless LAN (IEEE 802.11 a/b/g/n/ac)

CONSUMABLES

Toner (black)	13,500 prints
Toner (cyan/magenta/yellow)	10,000 prints
Waste toner bottle	11,000 sheets
Consumable yield measuring method	ISO/IEC 19798

For availability of models, options and software, please consult your local supplier.



Ricoh Europe (Netherlands) B.V.

John M. Keynesplein 10-B
1066 EP Amsterdam
The Netherlands

+31 (0)20 5774111

ricoh-europe.com