M C320FSE

MAIN SPECIFICATIONS

GENERAL	
Warm-up time	22 seconds
First copy speed: BW	7 seconds
First copy speed: full colour	14 seconds
Continuous output speed	A4/LEF (1-sided): : BW: 32 cpm, full colour: 32 cpm A4/LEF (2-sided): : BW: 16 cpm, full colour: 16 cpm
Memory: standard	0.5 GB
SPDF capacity	50 sheets
Weight	29.9 kg
Dimensions: W x D x H	410 x 429 x 483 mm
Power source	220 - 240 V, 50 - 60 Hz
COPIER	
Multiple copying	Up to 999 copies
Resolution	600 dpi
Zoom	From 25% to 400% in 1% steps
PRINTER	
First print speed: B/W	7.4 seconds
First print speed: full colour	8.4 seconds
CPU	833 Mhz
Printer language: standard	PCL6, PostScript 3 (emulation), PDF direct (emulation)
Print resolution	600 x 600 dpi
Network interface: standard	Ethernet 10 base-T/100 base-TX/1000 base-T, USB Host I/F Type A, USB Device I/F Type B, Bluetooth
Mobile printing capability	Apple AirPrint, Mopria®, Ricoh Smart Device Connector
Network protocol	TCP/IP
Windows® environments	Windows® 10, Windows® 11, Windows® Server 2016, Windows® Server 2019, Windows® Server 2022, Windows® Server 2025
Mac OS environments	Macintosh OS X v12 or later
SCANNER	
Scanning speed: SPDF (A4 LEF, 200dpi, B&W full colour)	30 ipm (simplex) - 42 ipm (duplex)
Resolution: maximum	600 dpi
File formats	Single Page TIFF, Single page JPEG, Single page PDF, Single page High compression PDF, Single page PDF/A, Multi page TIFF, Multi page PDF, Multi page High compression PDF, Multi page PDF/A, Single page Encryption PDF, Multi page Encryption PDF
Scan modes	E-mail, Folder, USB
FAX	
Circuit	PSTN, PBX
Transmission speed	3 seconds
Modem speed: maximum	33.6 Kbps
Compression method	MH, MR, MMR, JBIG
Scanning speed	30 spm
Memory: standard	2.5 MB (100 pages)
PAPER HANDLING	
Recommended paper size	Standard paper tray(s): A4, A5, A6, B5, B6 Optional paper tray(s) : A4, A5, B5, B6 Bypass tray: A4, A5, A6, B5, B6, Envelopes, Custom Size paper: Width: 76.2 mm - 216 mm, Length: 127 mm - 356 mm (Width: 76.2 mm - 216 mm, Length: 127 mm - 356 mm)
Paper input: standard	250 sheets
Paper input: bypass (standard)	50 sheets
Paper input: maximum	800 sheets
Paper output: standard	150 sheets
Paper weight	Trays: 60 - 200 g/m² Bypass: 60 - 200 g/m² Duplex: 60 - 163 g/m²
Paper types	Plain paper, Recycled paper, Special paper, Colour paper, Letterhead, Envelope, Label paper

M C320FSE

MAIN SPECIFICATIONS

ECOLOGY

Power consumption: max.	< 1,420 W
Power consumption operation: B&W	431.2 W
Power consumption operation: Full colour	452 W
Power consumption: ready	22.1 W
Power consumption: sleep	0.58 W
TEC*	0.33 kWh/week

* It is a reference value based on the ENERGY STAR Ver.3.2 test method.

INPUT/OUTPUT TRAYS AND FINISHER OPTIONS

1x 500-sheet paper tray

OTHER OPTIONS

Cabinet

CONSUMABLES

Toner (black)	10,500 prints
Toner (cyan/magenta/yellow)	7,500 prints
Consumable yield measuring method	ISO/IEC 19798

For availability of models, options and software, please consult your local supplier.

Ricoh UK Ltd.
800 Pavilion Drive
Northampton Business Park
NN4 7YL Northampton
United Kingdom

+44(0)1604 814900

www.ricoh.co.uk

RICOH
imagine. change.

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The images in this brochure are not real photographs and slight differences in detail might appear, including in relation to colour. Not all services and solutions are available to all customers. Copyright © 2026 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.