

P 502

MAIN SPECIFICATIONS

GENERAL

13 seconds Warm-up time First output speed: B/W 4.3 seconds Continuous output speed 43 ppm Memory: standard 2 GB HDD: maximum 320 GB Duplex Yes Weight 19.3 kg Dimensions: W x D x H 375 x 412 x 311 mm Power source 220 - 240 V, 50/60 Hz

















PRINTER

Network interface: option

Network protocol

Printer language: standard

PCL5e
PCL6
PostScript 3 (emulation)
PDF direct (emulation)
Printer language: option

Genuine Adobe® PostScript®3™

Genuine Adobe® PostScript®3™
IPDS
PDF Direct from Adobe®

Print resolution: maximum 1,200 x 1,200 dpi

Network interface: standard Ethernet 10 base-T/100 base-TX/1000 base-T

USB2.0 Type B

USB Host 2.0

Bi-directional IEEE 1284/ECP

Wireless LAN (IEEE 802.11a/b/g/n)

Additional NIC (2nd port)

Additional NIC (2nd port)

Mobile printing capability

Apple AirPrint

Mopria®

Google Cloud Print

Google Cloud Print NFC Ricoh Smart Device Connector TCP/IP (IP v4, IP v6)

Windows® environments

Windows® 7
Windows® 8.1
Windows® 10
Windows® Server 2008
Windows® Server 2008
Windows® Server 2012
Windows® Server 2012
Windows® Server 2012R2
Windows® Server 2012R2
Windows® Server 2016
Wac OS environments

Macrintesh OS X v10.10 or later

SAP® environments

SAP® R/3®, SAP® S/4®

Other supported environments

NDPS Gateway

AS/400® using OS/400 Host Print Transform

SAP® R/3®, SAP® S/4® NDPS Gateway AS/400® using OS/400 Host Print Transform Device Option Utility (Citrix) Linux environment

PAPER HANDLING

A4, A5, A6, B5, B6 Recommended paper size Paper input: standard 500 sheets Paper input: bypass 100 sheets Paper input: maximum 2 100 sheets Paper output: standard 250 sheets Trays: (52 - 220 g/m²), Bypass: (52 - 256 g/m²), Duplex: (52 - 162 g/m²) Paper weight Paper types Plain paper Recycle paper Preprinted paper Envelope Label paper

ECOLOGY

 Power consumption: max.
 Less than 1,260 W

 TEC*
 0.54 kWh

* It is a reference value based on early to enter d (E) e Anger/ DE-U2-205) imagine. Change, INPUT/OUTPUT TRAYS AND FINISHER OPTIONS

3x 250-sheet Paper tray 3x 500-sheet Paper tray

OTHER OPTIONS

Hard Disk Drive VM card IPDS unit Genuine PostScript 3 IEEE 1284 I/F IEEE 802.11 a/b/g/n I/F USB Device Server

CONSUMABLES

Starter toner 17,400 prints

ISO9001 certified, ISO14001 certified, ISO27001 certified

All brand and/or product names are trademarks of their respective owners.

Specifications and external appearance are subject to change without notice. The images in this brochure are not real photographs and slight differences in detail might appear, including in relation to colour. Not all services and solutions are available to all customers.

Copyright © 2025 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.